



OPTIMUS₂TM

Workforce management, intelligently

OPTIMUS₂ — On the outside, a large, easy-to-read color display and familiar ATM style interface. On the inside, functionality far beyond old fashioned time & attendance and payroll terminals. The OPTIMUS₂ is a full-service/self-service terminal that allows for both the input and output of information to help HR professionals manage their business.

The OPTIMUS₂ packs a powerful processor and open programming, so UCS and/or Java™ development is a snap to deploy. The biometric option protects employees' personal information and eliminates costly buddy-punching.

The OPTIMUS₂ — the new solution for human asset management.

OPTIMUS₂TM features include:

- Large, easy-to-read color display
- Familiar ATM-style interface – self service functionality
- Biometric options
- Modular, field-upgradeable readers
- Internal USB port
- Works in WAN and LAN environments
- On-board and remote diagnostics
- Optional GSM/GPRS modem
- Optional transmissive color touchscreen
- Optional power-over-Ethernet module



To learn more about ATS and OPTIMUS₂, visit www.accu-time.com or call +1 860.870.5000.

A member of the **Global** series

Specifications

DISPLAY 320 x 240 pixel QVGA transmissive color LCD (optional transmissive color touchscreen)
CLOCK Battery-backed real-time clock, 12- or 24-hour format (quartz precision)
KEYPAD Ten software-defined function keys
Numeric keypad, 0-9
In and Out keys
Scroll and select keys

MEMORY 128 MB RAM and 128 MB flash

PROGRAMMING Java™ option
Web services capable
ATS Universal Command Set or third-party custom application packages

PLATFORM Linux®
DIAGNOSTICS On-board diagnostics, and remote diagnostic capability
INTERFACE Standard 802.3 10/100 BASE-T Ethernet with DHCP
Optional EIA standard RS232
Optional internal modem (FCC Part 68 certified)
Optional GSM/GPRS modem
USB port for mass storage device

ENCLOSURE Advanced composite enclosure
Molded-in color

POWER 12 VDC (nominal) 1.25A, 15W maximum
Optional uninterruptible power supply with charger
Optional IEEE 802.3af-compliant power over Ethernet

ENVIRONMENT Operation Temperature: 0° to 50°C (32° to +122°F)
Storage Temperature: -20° to 80°C (-4° to +176°F)

PHYSICAL 30.0 cm x 21.6 cm x 9.4 cm (11.8" x 8.5" x 3.7")

CERTIFICATIONS CE Mark, FCC Part 15 Class A

ACCESSORIES

- Biometric readers – 1:1 and 1:n – fingerscan
- Integrated visible or infrared barcode readers
- Integrated magnetic stripe readers
- Smartcard readers – contactless (Mifare™, iClass®)
- Integrated proximity readers
- Solid-state or dry-contact relay modules
- Serial interface for optional printer

Accu-Time Systems, Inc.

One Accu-Time Plaza
Route 83
Ellington, CT 06029

TEL: +1 (860) 870-5000

FAX: +1 (860) 872-1511

Toll Free: 1-800-355-4648

sales@accu-time.com

www.accu-time.com

Accu-Tech Systems, Ltd.

C1 Caerphilly Business Park
Caerphilly
Mid Glamorgan
CF83 3ED
United Kingdom

TEL: +44 (0) 2920 885599

FAX: +44 (0) 2920 868666

Continental Europe

TEL: +31 (0) 318 75 41 33

Latin America

ventas@accu-time.com

TEL: +1 (617) 573-5073



All of the ATS
Global Series
products are
100% RoHS
compliant



AN **AMANO**. GROUP COMPANY

To learn more about ATS, visit www.accu-time.com or call +1 860-870-5000.
As part of Accu-Time's continuous improvement process, we reserve the right to change product specifications without notice.