



## Prodigy™

### *Workforce management, affordably*

Prodigy™ — ideal blend of performance, function, style, and affordability designed for essential workforce management functionality.

Prodigy is for those who demand a rich suite of features at an affordable price: Web services, customizable function keys, optional biometrics, smartcards, and more!

Biometric options protect employees' personal information and eliminate costly buddy-punching.

#### Prodigy™ features include:

- Internet appliance
- On-board and remote diagnostics
- Biometric options for increased personal security
- Programmable function keys
- Ergonomic design with angled card slot
- Works in WAN and LAN environments
- Optional GSM/GPRS modem
- Optional power-over-Ethernet module



*USB drive  
not included*

To learn more about ATS and Prodigy,  
visit [www.accu-time.com](http://www.accu-time.com) or call +1 860.870.5000.

A member of the **Global** series

## Specifications

**DISPLAY** 128 x 32 pixel LCD  
**CLOCK** Battery-backed real-time clock, 12- or 24-hour format (quartz precision)  
**KEYPAD** 16-key tactile 4x4 matrix  
Numeric keypad, 0-9  
Two software-defined function keys  
In/Out and Clear/Enter keys  
Customizable overlay allows for unique graphic options

**MEMORY** Linux: 16 MB RAM and 32 MB flash  
Optional Java: 128 MB RAM and 128 MB flash

**PROGRAMMING** Java™ option  
Web services capable  
ATS Universal Command Set or third-party custom application packages

**PLATFORM** Linux®  
**DIAGNOSTICS** On-board diagnostics, and remote diagnostic capability  
**INTERFACE** Standard 802.3 10/100 BASE-T Ethernet with DHCP  
Optional EIA standard RS232  
Optional internal modem (FCC Part 68 certified)  
Optional GSM/GPRS modem  
USB port for mass storage device

**ENCLOSURE** Advanced composite enclosure  
**POWER** 12 VDC (nominal) 1.25A, 15W maximum  
Optional uninterruptible power supply with charger  
Optional IEEE 802.3af-compliant power over Ethernet

**ENVIRONMENT** Operation Temperature: 0° to 50°C (32° to +122°F)  
Storage Temperature: -20° to 80°C (-4° to +176°F)

**PHYSICAL** 18.4 cm x 21.3 cm x 9.65 cm (7.25" x 8.40" x 3.80")  
**CERTIFICATIONS** CE Mark, FCC Part 15 Class A  
**ACCESSORIES**

- Biometric readers – 1:1 and 1:n – fingerscan
- Integrated visible or infrared barcode readers
- Integrated magnetic stripe readers
- Smartcard readers – contactless (Mifare™, iClass®)
- Integrated proximity readers
- Solid-state or dry-contact relay modules
- Serial interface for printer

### Accu-Time Systems, Inc.

One Accu-Time Plaza  
Route 83  
Ellington, CT 06029

**TEL: +1 (860) 870-5000**

**FAX: +1 (860) 872-1511**

**Toll Free: 1-800-355-4648**

**sales@accu-time.com**

**www.accu-time.com**

### Accu-Tech Systems, Ltd.

C1 Caerphilly Business Park  
Caerphilly  
Mid Glamorgan  
CF83 3ED  
United Kingdom

**TEL: +44 (0) 2920 885599**

**FAX: +44 (0) 2920 868666**

### Continental Europe

**TEL: +31 (0) 318 75 41 33**

### Latin America

**ventas@accu-time.com**

**TEL: +1 (617) 573-5073**



All of the ATS  
Global Series  
products are  
100% RoHS  
compliant



AN **AMANO**. GROUP COMPANY

To learn more about ATS, visit [www.accu-time.com](http://www.accu-time.com) or call +1 860-870-5000.  
As part of Accu-Time's continuous improvement process, we reserve the right to change product specifications without notice.