

Workforce management, intelligently

A member of the **Global** series



Prodigy™ — The ideal blend of performance, function, style, and affordability designed for essential workforce management functionality.

Prodigy is for those who demand a rich suite of features at an affordable price: plug and play, Web services, customizable function keys, optional biometrics, smartcards, and more!

Biometric options protect employees' personal information and eliminate costly buddy-punching.

Prodigy features include:

- Internet appliance
- Plug and play
- On-board and remote diagnostics
- Biometric options for increased personal security
- Programmable function keys
- Ergonomic design with angled card slot
- Works in WAN and LAN environments, including GSM/GPRS modem and Ethernet
- Optional power-over-Ethernet module

Answers for HR Professionals™

AN **AMANO** GROUP COMPANY





Specifications

DISPLAY	128 x 32 pixel LCD
CLOCK	Battery-backed real-time clock, 12- or 24-hour format, USA or international (quartz precision)
KEYPAD	16-key tactile 4x4 matrix Numeric keypad, 0-9 Two software-defined function keys In/Out and Clear/Enter keys Customizable overlay allows for unique graphic options
MEMORY	Linux: 16 MB RAM and 32 MB flash Optional Java: 128 MB RAM and 128 MB flash
PROGRAMMING	Java™ option Web services capable ATS Universal Command Set or third-party custom application packages
PLATFORM	Linux®
DIAGNOSTICS	On-board diagnostics, and remote diagnostic capability
INTERFACE	Standard 802.3 10/100BASE-T Ethernet with DHCP Optional EIA standard RS232 Optional internal modem (FCC Part 68 certified) Optional GSM/GPRS modem USB port for mass storage device
ENCLOSURE	Advanced composite enclosure
POWER	12 VDC (nominal) 1.25A, 15W maximum Optional uninterruptible power supply with charger Optional IEEE 802.3af-compliant power over Ethernet
ENVIRONMENT	Operating temperature: 0° to 50°C (32° to +122°F) Storage temperature: -20° to 80°C (-4° to +176°F)
PHYSICAL	18.4 cm x 21.3 cm x 9.65 cm (7.25" x 8.40" x 3.80")
CERTIFICATIONS	CE Mark, FCC Part 15 Class A
ACCESSORIES	<ul style="list-style-type: none">• Biometric readers – 1:1 and 1:n – fingerscan• Integrated visible or infrared bar code readers• Integrated magnetic readers• Smartcard readers – contactless (Mifare™ and iClass®)• Integrated proximity readers• Solid-state or dry-contact relay modules• Serial interface for printer

To learn more about ATS visit www.accu-time.com.

As part of Accu-Time's continuous improvement process, we reserve the right to change product specifications without notice.

Accu-Time Systems, Inc.

One Accu-Time Plaza
Route 83
Ellington, CT 06029

1-800-355-4648

sales@accu-time.com

www.accu-time.com

TEL: (860) 870-5000

FAX: (860) 872-1511

EMAIL: sales@accu-time.com

Accu-Tech Systems Ltd

C1 Caerphilly Business Park
Caerphilly
Mid Glamorgan
CF83 3ED
United Kingdom

EMEA

+44 (0) 2920 885599

enquire@accu-tech.co.uk

www.accu-tech.co.uk

Continental Europe

+31 (0) 318 75 41 33

Latin America

ventas@accu-time.com

Connecticut • Chicago • Sarasota • Boston • United Kingdom • Netherlands



All of the ATS
Global Series
products are
100% RoHS
compliant